

## RJ Tech Steinadler Pro Specifications

	<b>Steinadler Pro 4WD</b>	<b>Steinadler Extender 4WD</b>
<b>Battery Type</b>	1x Lithium NCM 70V 64Ah	1x Lithium NCM 70V 64Ah
<b>Battery Capacity</b>	4.5kWh	4.5kWh
<b>E-range</b>	100km 62mi	220 km 137mi
<b>Motor Type</b>	4x 5kW PMSM Hub Motor	4x 5kW PMSM Hub Motor
<b>Max. Power</b>	20kW	20kW
<b>Max. speed</b>	85 km/h	90 km/h
<b>Rated Torque</b>	520 N·m	540 N·m
<b>Peak Torque</b>	610 N·m	630 N·m
<b>Range Extender Power</b>	/	1.5kW
<b>Dimension L*W*H</b>	1820x885x1327mm	1820x885x1327mm
<b>Fold Size L*W*H</b>	1820x885x732mm	1820x885x732mm
<b>Ground Clearance</b>	220mm	220mm
<b>Offroad Tyre Size</b>	560mm	560mm
<b>Curb Weight</b>	190kg	205kg
<b>Load Capacity</b>	200kg	200kg
<b>Tow Capacity</b>	400kg (weight)	600kg (weight)
<b>Max. Climbing Slope</b>	63°	63°
<b>Max. Tunting Angle</b>	33°	33°
<b>Max. Rolling Angle</b>	30°	30°

	<b>Steinadler Pro 4WD</b>	<b>Steinadler Extender 4WD</b>
<b>Min. Turning Radius</b>	0.9m (tank turn)	0.9m (tank turn)
<b>Accelerate (0-50kph)</b>	2.3s	2.3s
<b>Foldable</b>	Yes	Yes
<b>Speed Switch</b>	3 levels	3 levels
<b>Escape mode</b>	Yes	Yes
<b>Smart Display</b>	Yes	Yes
<b>LED Light</b>	Yes	Yes
<b>Charger Set</b>	Yes	Yes
<b>Charger I/O</b>	110V-230V 50Hz	110V-230V 50Hz
<b>Charging Time</b>	3h (from 0% to 100%)	3h (from 0% to 100%)
<b>Retractable Seat</b>	Yes	Yes
<b>Mudguard</b>	Optional	Optional
<b>Butterfly Handlebar</b>	Optional	Optional
<b>Range Extender</b>	/	Yes

\*Clarification: All parameters have been tested and verified by RJ Tech Limited. Specific modifications may be required based on varying laws and regulations in different countries or regions. RJ Tech Limited reserves the rights to interpret and explain product specifications.

\*\*This vehicle can experience decreased performance in low temperature environments due to increased strain on batteries, which the use of a range extender is recommended.